

All American Front Engine

ACTIVITY/MFSAB*

Blue Bird builds reliable buses.



The All American's totally redesigned driver's area includes a high-back seat to maximize comfort.



The All American features optional underfloor luggage with locking doors.



Features:

- Seating for up to 56 passengers
- Flat front transit-style design
- Complete entrance visibility
- Roomy underfloor luggage bays in a variety of sizes and locations for safe and convenient storage
- Excellent driver ergonomics with a wraparound dash console and high-back seat
- Easy passenger entry
- Convenient service access
- Unrivaled strength, safety, and durability of Blue Bird's renowned unitized body construction
- Acoustical ceiling panels standard to reduce noise
- Durable baked polyurethane paint



BLUE BIRD

Reliable Since 1927

ALL AMERICAN
BLUE BIRD

* MFSAB - Multifunction School Activity Bus

Activity/MFSAB* All American Front Engine Specifications

Blue Bird builds reliable buses.



Reliable since 1927

CHASSIS

- 50,000 psi steel frame rails 9 5/8" high x 3" flanges x 1/4" thick
- Allison® automatic transmission, PTS 2500
- Synthetic transmission fluid
- 60 gal. fuel tank between frame rails in rear overhang
- 175 amp Leece/Neville®, "High Output" alternator
- 11R22.5 Michelin® XZE, highway tread tires
- Large, easy to read gauges
- 13,200 lb. front axle with heavy-duty 2 leaf parabolic spring suspension
- 21,000 lb. rear axle with a two-stage, rear suspension system
- Long life coolant, -40° F
- Black rubber coolant hoses with constant torque clamps
- Meritor® "Quadraulic" hydraulic brake system
- Anti-lock brakes
- 12" steel front bumper
- Tilt/telescoping steering wheel
- Three "Group 3" batteries (2100 CCA)
- "Huck spin" fasteners on all permanent frame fixtures

DURABILITY

- All parts are pre-primed or thoroughly rust-proofed after fabrication and before assembly
- Entire underbody (body skirt and floor) is undercoated before mounting on chassis
- Exterior surfaces are painted w/ heat-cured polyurethane
- Interior surfaces are painted w/ high-quality, hotsprayed, baked-on enamel
- 1/2" fir grade plywood screwed down for insulation of the floor
- 1/8" Smooth black rubber flooring, 3/16" ribbed rubber aisle
- Goodyear Hi-Miler heater hose w/ constant torque clamps
- Black rubber cooling hoses w/ constant torque clamps
- Synthetic transmission fluid
- Michelin® Tires
- Spicer "lubed for life" driveline
- Rubber molded wheelhouse
- Stainless steel stepwell
- 13,200 lb front axle with heavy-duty 2 leaf parabolic spring suspension
- 21,000 lb. rear axle with a two-stage, rear suspension system
- Side exhaust before rear wheels
- "Huck spin" frame fasteners

STRENGTH

- 14-gauge steel, hat shaped posts and roof bows
- Rigid 16-gauge steel roof longitudinal internal structural members
- 16-gauge channeled interior steel window headers
- A massive 16-gauge continuous belt of interior steel armor above and below floor line
- Riveted and welded construction
- Four full-length, 16 gauge exterior side rub rails
- 20-gauge fluted exterior side panels
- 22-gauge interior galvalume side panels
- 14-gauge steel floor panels
- 50,000 psi steel chassis frame with permanent fixtures and attached with huck spin fasteners

SAFETY

- 4-wheel anti-lock brakes
- Dual halogen headlights
- Driver's three-point seat belt w/ adjustable 7 1/2" pillar loop
- "Full view" outward-opening entrance door w/ 1,350 square-inch tempered safety glass
- Three step, stainless steel stepwell
- Daytime running lights
- 9" x 17" oval-shaped, flat and convex rearview mirrors
- 11" x 13" oval shape crossover mirrors w/ tinted band to reduce glare
- Electric horn w/ high and low note.
- Blue Bird's unitized construction of the passenger compartment
- 12" steel front bumper, 12" steel rear bumper (Double "X" braced)
- Side exhaust, before rear wheels
- 8.25 x 22.5 Disc, hub-piloted steel wheels
- Michelin® 11R22.5(H) tires

SERVICEABILITY

- Body wiring terminal is easily accessible through exterior electrical compartment
- Wiring is color coded and continuously numbered for easy identification
- Automatic resetting circuit breakers for body wiring
- Tempered glass, split-sash windows
- Grease fittings on emergency door hinges
- Long life coolant, -40° F
- Easy-opening, outward opening entrance door; features long-lasting, oil-impregnated, bronze pivotal bearings
- Body wiring is encased in "easy to access" ABS molding above passenger windows
- All access panels include keyed-locked latches
- Side exit exhaust
- Stainless steel stepwell-bolted

DRIVER ERGONOMICS

- Power steering with tilt/telescoping column
- Large, easy to read gauges
- Backlit, easy to reach switch panel w/ rocker switches
- Electric, intermittent, single switch windshield wipers
- High-back, charcoal fabric, adjustable driver's seat
- Manual "glide-type" outward opening door
- 3-point seat belt with 7 1/2" vertical adjustment
- National® fully adjustable driver's seat
- Cruise control
- Dash digital clock

COMFORT & CONVENIENCE

- 74" headroom at aisle, front to rear
- Split-sash, tempered windows
- Shaded windshield
- 90,000 btu front heater and defroster
- Power accessory socket for cellular phones, CB radios, etc.
- 1/2" fir grade plywood, screwed down for insulation of the floor
- Full "panoramic" cockpit view
- Full body insulation
- Acoustic headlining (Driver's and 1st sections)

OPTIONAL FEATURES

- Caterpillar® C7 ACERT diesel engine; 190-275 hp
- Cummins® ISB-02 diesel engine; 200-260 hp
- Allison® PTS 2200 & PTS 3000 Transmission
- Hendrickson® front and rear air ride suspension
- Electric, remote control and heated mirrors
- Laminated glass
- 77" headroom/12" split sash windows
- Dedicated door and wheelchair lifts, along w/ recessed wheelchair securements for special-needs passengers
- Underfloor luggage compartments w/ locking doors
- Tinted glass
- Mud flaps
- Vandal locks
- AM/FM/CD Radio w/ deluxe speakers
- 100 gallon fuel tank
- Air brake system

DIMENSIONS

• Headroom.....	74"
• Width exterior	96"
• Width interior	90 3/4"
• Skirt length	19 3/4"
• Overall length.....	289"- 471"
• Overall height.....	124"-127"
• Wheelbase	141"
.....	169"
.....	190"
.....	211"
.....	232"

Blue Bird Corporation

402 Blue Bird Blvd.

P.O. Box 937

Fort Valley, GA 31030

1-478-822-2767

www.blue-bird.com



BLUE BIRD

* Activity Bus: Any motorized vehicle that has a seating capacity of 11 persons or more and is not a school bus

* MFSAB: A school bus without warning lights, stop arm, and can be a color other than yellow. The bus cannot be used for home to school transportation or in any situation that would require the controlling of traffic.

Specifications shown were in effect on the date they were approved for printing. In keeping with its policy of continual product improvement, Blue Bird reserves the right to change specifications without notice and without incurring obligations. Some equipment and features shown may be optional—your Blue Bird Distributor will explain.